

BOLZANO-3.1

BOLZANO-3.2

BOLZANO-3.3

BOLZANO-3.4


BOLZANO-III

EN

The BRIDGELUX-LED 6.5W/8.5W Architectural Lighting offers energy-efficient and versatile illumination for various applications. With LED power ranging from 6.5W to 8.5W and system output of 514lm to 668lm, it ensures reliable and bright performance. Beam angles of 15°, 24°, 36°, and 60° provide flexibility for both focused and wide lighting needs. Supporting a CCT range of 2700K to 6000K, with a standard 3000K for warm, natural lighting, it delivers exceptional color accuracy with CRI > 90. Rated IP20 and IP54 for durability, it integrates seamlessly into various environments. Control options include On/Off, DALI, 0/1-10V, and TRIAC. Available in white or black front rings, it features optical protection options like honeycomb louver, spread, diffusion, and clear lenses for enhanced versatility.

IT

L'illuminazione architettonica BRIDGELUX-LED 6,5W/8,5W offre un'illuminazione versatile ed efficiente dal punto di vista energetico per varie applicazioni. Con una potenza del LED compresa tra 6,5 W e 8,5 W e un'uscita del sistema compresa tra 514 lm e 668 lm, garantisce prestazioni affidabili e luminose. Gli angoli del fascio di 15°, 24°, 36° e 60° offrono flessibilità sia per le esigenze di illuminazione focalizzata che per quella ampia. Supportando una gamma CCT da 2700K a 6000K, con uno standard di 3000K per un'illuminazione calda e naturale, offre un'eccezionale precisione del colore con CRI > 90. Classificato IP20 e IP54 per una maggiore durata, si integra perfettamente in vari ambienti. Le opzioni di controllo includono On/Off, DALI, 0/1-10V e TRIAC. Disponibile con anelli frontali bianchi o neri, è dotato di opzioni di protezione ottica come feritoia a nido d'ape, diffusione, diffusione e lenti trasparenti per una maggiore versatilità.

Reference: System Power - Output Lumen - Delivered Lumen - Beam Angle

BOLZANO-3.1	C919	8W - 814lm - 514lm - 15°	C920	8W - 814lm - 528lm - 24°	C921	8W - 814lm - 545lm - 36°	C922	8W - 814lm - 524lm - 45°
	C923	10W - 976lm - 561lm - 15°	C924	10W - 976lm - 623lm - 24°	C925	10W - 976lm - 668lm - 36°	C926	10W - 976lm - 644lm - 45°
BOLZANO-3.2	C927	11W - 951lm - 694lm - 15°	C928	11W - 951lm - 720lm - 24°	C929	11W - 951lm - 751lm - 36°	C930	11W - 951lm - 700lm - 50°
	C931	13W - 1087lm - 811lm - 15°	C932	13W - 1087lm - 842lm - 24°	C933	13W - 1087lm - 878lm - 36°	C934	13W - 1087lm - 819lm - 50°
BOLZANO-3.3	C935	20W - 2343lm - 1537lm - 15°	C936	20W - 2343lm - 1626lm - 24°	C937	20W - 2343lm - 1617lm - 36°	C938	20W - 2343lm - 1512lm - 60°
	C939	25W - 2569lm - 1844lm - 15°	C940	25W - 2569lm - 1951lm - 24°	C941	25W - 2569lm - 1940lm - 36°	C942	25W - 2569lm - 1814lm - 60°
BOLZANO-3.4	C943	30W - 2940lm - 2351lm - 15°	C944	30W - 2940lm - 2549lm - 24°	C945	30W - 2940lm - 2548lm - 36°	C946	30W - 2940lm - 2405lm - 60°
	C947	35W - 3974lm - 2150lm - 15°	C948	35W - 3974lm - 2982lm - 24°	C949	35W - 3974lm - 2981lm - 36°	C950	35W - 3974lm - 2813lm - 60°

Finish	CCT/CRI		IP	Dim		Emergency	Colour (Reflect or)
	K1 - 2700K /90	K2 - 3000K /90		A - On/Off	B - DALI		
W - WHITE	K1 - 2700K /90	K2 - 3000K /90	1 - IP20	A - On/Off	B - DALI	Y - Yes	TU - TUBE
B - BLACK	K3 - 3500K /90	K4 - 4000K /90	2 - IP54	C - 0/1-10v	D - TRIAC	N - No	
	K5 - 5000K /90	K6 - 2700-6000K /90		E - BLUETOOTH	F - ZIGBEE		
				G - CASAMBI			


Code Example

A001 TA W K11 A Y


Enter Your Code:

CODE FINISH CCT IP DIM EMERGENCY


10W/15°/3000K/Ra90




10W/24°/3000K/Ra90




10W/36°/3000K/Ra90




10W/45°/3000K/Ra90




30W/15°/3000K/Ra90




11W/15°/3000K/Ra90




11W/24°/3000K/Ra90




11W/36°/3000K/Ra90




11W/50°/3000K/Ra90




30W/24°/3000K/Ra90




25W/15°/3000K/Ra90




25W/24°/3000K/Ra90




25W/36°/3000K/Ra90



25W/60°/3000K/Ra90



30W/36°/3000K/Ra90



Optical Accessories

OR01



Honeycomb Louver

OR02



Spread Lens

OR03



Diffusion Lens

OR04



Clear Lens