



LATINA L-1.1




TR - Trim Fixed

LATINA L-1.2




TR - Trim Adjustable

LATINA L-1.3




TR - Trim Adjustable

LATINA L-1.4



TR - Trim Adjustable

LATINA L-1.5



TR - Trim Adjustable

LATINA L-I

EN

The BRIDGELUX LED 6.5W/8.5W Architectural Lighting offers flexible and efficient lighting for a variety of spaces. With LED power ranging from 6.5W to 8.5W and system power from 8W to 10W, it provides LED output from 814lm to 976lm and system output ranging from 470lm to 589lm. Available in beam angles of 15°, 24°, and 36°, and a CRI > 90 for excellent color rendering. The standard CCT is 3000K, with options ranging from 2700K to 6000K. Powered by a 34V 200mA to 250mA drive, it features black, satin silver, and silver reflectors and comes with white or black front rings. IP20 rating and On/Off, DALI, 0/1-10V, and TRIAC controls.

IT

L'illuminazione architettonica BRIDGELUX LED 6,5W/8,5W offre un'illuminazione flessibile ed efficiente per una varietà di spazi. Con una potenza dei LED compresa tra 6,5 W e 8,5 W e una potenza del sistema compresa tra 8 W e 10 W, fornisce un'uscita LED da 814 lm a 976 lm e un'uscita del sistema compresa tra 470 lm e 589 lm. Disponibile con angoli di emissione di 15°, 24° e 36° e un CRI > 90 per un'eccellente resa cromatica. Il CCT standard è 3000K, con opzioni che vanno da 2700K a 6000K. Alimentato da un azionamento da 34 V da 200 mA a 250 mA, è dotato di riflettori neri, argento satinato e argento e viene fornito con anelli frontali bianchi o neri. Grado di protezione IP20 e controlli On/Off, DALI, 0/1-10V e TRIAC.

Reference: System Power - Output Lumen - Delivered Lumen - Beam Angle

LATINA L-1.1	C291	8W - 814lm - 470lm - 15°	C292	8W - 814lm - 481lm - 36°	C293	8W - 814lm - 517lm - 24°	C294	10W - 976lm - 553lm - 15°
	C295	10W - 976lm - 589lm - 24°	C296	10W - 976lm - 546lm - 36°				
LATINA L-1.2	C297	8W - 814lm - 470lm - 15°	C298	8W - 814lm - 517lm - 24°	C299	8W - 814lm - 481lm - 36°	C300	10W - 976lm - 553lm - 15°
	C301	10W - 976lm - 589lm - 24°	C302	10W - 976lm - 546lm - 36°				
LATINA L-1.3	C303	8W - 814lm - 492lm - 15°	C304	8W - 814lm - 525lm - 24°	C305	8W - 814lm - 484lm - 36°	C306	10W - 976lm - 550lm - 15°
	C307	10W - 976lm - 593lm - 24°	C308	10W - 976lm - 544lm - 36°				
LATINA L-1.4	C309	8W - 814lm - 292lm - 15-50°	C310	10W - 976lm - 365lm - 15-50°				
LATINA L-1.5	C311	8W - 814lm - 514lm - 15°	C312	8W - 814lm - 528lm - 24°	C313	8W - 814lm - 545lm - 36°	C314	8W - 814lm - 524lm - 45°
	C315	10W - 976lm - 561lm - 15°	C316	10W - 976lm - 623lm - 24°	C317	10W - 976lm - 668lm - 36°	C318	10W - 976lm - 644lm - 45°

Mode	Finish	CCT/CRI		IP	Dim		Emergency	Colour (Reflector)	
TR Trim Version	W - WHITE	K5 - 5000K /90	K4 - 4000K /90	1 - IP20	A - On/Off	B - DALI	Y- Yes	B - BLACK	SS - SATIN SILVER
	B - BLACK	K3 - 3500K /90	K2 - 3000K /90	2 - IP54	C - 0/1-10v	D - TRIAC	N- No	S - SILVER	
		K1 - 2700K /90			E - BLUETOOTH H	F - ZIGBEE			
					G - CASAMBI				


Code Example

A001 TA W K11 A Y


Enter Your Code:

CODE MODE FINISH CCT IP DIM EMERGENCY


8W/15°/3000K/Ra90




8W/24°/3000K/Ra90




8W/36°/3000K/Ra90




10W/15°/3000K/Ra90




10W/24°/3000K/Ra90




10W/36°/3000K/Ra90




10W/15°/3000K/Ra90




10W/24°/3000K/Ra90



10W/36°/3000K/Ra90



10W/45°/3000K/Ra90



Optical Accessories

OR01



Honeycomb Louver

OR02



Spread Lens

OR03



Diffusion Lens

OR04



Clear Lens

Colour(Reflector)



Black



Satin Silver



Silver